

Flavor West Manufacturing, LLC. Version No: 1.1

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 2

Issue Date: 04/27/2021

Print Date: 04/27/2021 Initial Date: 04/27/2021 L.GHS.USA.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	FW-WCH N&A Wild Cherry Flavor
Synonyms	Not Available
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified	Use according to manufacturer's directions.
uses	

Details of the manufacturer/importer

Registered company name	Flavor West Manufacturing, LLC.
Address	29400 Hunco Way, Lake Elsinore CA 92530 United States
Telephone	(951) 893-5120
Fax	(714) 276-1621
Website	www.FlavorWest.com
Email	Flavor@FlavorWest.com

Emergency telephone number

Association / Organisation	Chemwatch
Emergency telephone numbers	see below
Other emergency telephone numbers	see below

CHEMWATCH EMERGENCY RESPONSE

Primary Number	Alternative Number 1	Alternative Number 2
877 715 9305	+612 9186 1132	Not Available

Once connected and if the message is not in your prefered language then please dial 01

Una vez conectado y si el mensaje no está en su idioma preferido, por favor marque 02

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture



GHS Classification	Eye Irritation Category 2B, Flammable Liquid Category 4

Label elements

GHS label elements	Not Applicable
SIGNAL WORD	WARNING

Hazard statement(s)

H320	Causes eye irritation
H227	Combustible liquid

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	

Precautionary statement(s) Response

P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam for extinction.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337+P313	If eye irritation persists: Get medical advice/attention.	

Precautionary statement(s) Storage

P403+P235 Store in a well-ventilated place. Keep cool.

Precautionary statement(s) Disposal P501 Dispose of conten

Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
57-55-6	90-99	propylene glycol

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST AID MEASURES

Description of first aid measures	
Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available).

	 Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

- Polyethylene glycols are generally poorly absorbed orally and are mostly unchanged by the kidney.
- Dermal absorption can occur across damaged skin (e.g. through burns) leading to increased osmolality, anion gap metabolic acidosis, elevated calcium, low ionised calcium, CNS depression and renal failure.

Treatment consists of supportive care.

[Ellenhorn and Barceloux: Medical Toxicology]

Propylene glycol is primarily a CNS depressant in large doses and may cause hypoglycaemia, lactic acidosis and seizures.

- The usual measures are supportive care and decontamination (Ipecac/ lavage/ activated charcoal/ cathartics), within 2 hours of exposure should suffice.
- Check the anion gap, arterial pH, renal function and glucose levels.

Ellenhorn and Barceloux: Medical Toxicology

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

 Alcohol stable foam. Dry chemical powder. BCF (where regulations permit). Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	---

Advice for firefighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area.
Fire/Explosion Hazard	 Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO).

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment.
Major Spills	Chemical Class: alcohols and glycols For release onto land: recommended sorbents listed in order of priority.

cross-linked polymer - pillow1throwpisorbent clay - particulate2shovelshwood fiber - pillow3throwpitreated wood fiber - pillow3throwpifoamed glass - pillow4throwpiLAND SPILL - MEDIUM4throwpicross-linked polymer - particulate1blowerskiplopolypropylene - particulate2blowerskiplosorbent clay - particulate2blowerskiplopolypropylene - mat3throwskiplopolypropylene - mat3blowerskiplopolyurethane - mat4throwskiploLegendDGC: Not effective where ground cover is denseR; Not reusableI: Not incinerableP: Effectiveness reduced when rainyRT:Not effective where terrain is ruggedSS: Not for use within environmentally sensitive sitesW: Effectiveness reduced when windyReference: Sorbents for Liquid Hazardous Substance Cleanup and Control;	SORBENT TYPE	RANK	APPLICATION			COLLECT	ΓΙΟΝ	LIMITATIONS
cross-linked polymer - pillow1throwpisorbent clay - particulate2shovelstwood fiber - pillow3throwpitreated wood fiber - pillow3throwpifoamed glass - pillow4throwpiLAND SPILL - MEDIUM4throwpicross-linked polymer - particulate1blowerskiplopolypropylene - particulate2blowerskiplosorbent clay - particulate2blowerskiplopolypropylene - mat3throwskiplopolypropylene - mat3blowerskiplopolyurethane - mat4throwskiploLegendDGC: Not effective where ground cover is denseR; Not reusableI: Not incinerableP: Effectiveness reduced when rainyRT:Not effective where terrain is ruggedSS: Not for use within environmentally sensitive sitesW: Effectiveness reduced when windyReference: Sorbents for Liquid Hazardous Substance Cleanup and Control;	LAND SPILL - SMALL							
sorbent clay - particulate2shovelshwood fiber - pillow3throwpitreated wood fiber - pillow3throwpifoamed glass - pillow4throwpiLAND SPILL - MEDIUM4throwpicross-linked polymer - particulate1blowerskiplepolypropylene - particulate2blowerskiplesorbent clay - particulate2blowerskiplepolypropylene - mat3throwskiplepolypropylene - mat3blowerskiplepolypropylene - mat4throwskiplepolypropylene - mat3blowerskiplepolypropylene - mat4throwskiplepolypropylene - mat4throwskiplepolypropylene - mat3blowerskiplepolypropylene - mat4throwskiplepolypropylene - mat4throwskiplepolycrethane - mat4throwskipleLegendDGC: Not effective where ground cover is denseskipleP: Effectiveness reduced when rainyR: Not incinerableskipleP: Effectiveness reduced when rainyS: Not for use within environmentally sensitive sitesskipleW: Effectiveness reduced when windyReference: Sorbents for Liquid Hazardous Substance Cleanup and Control;skiple	cross-linked polymer	- particulate		1		shovel	shovel	R, W, SS
wood fiber - pillow3throwpitreated wood fiber - pillow3throwpifoamed glass - pillow4throwpiLAND SPILL - MEDIUM4throwpicross-linked polymer - particulate1blowerskiplopolypropylene - particulate2blowerskiplosorbent clay - particulate2blowerskiplopolypropylene - mat3throwskiploexpanded mineral - particulate3blowerskiplopolyurethane - mat4throwskiploLegendDGC: Not effective where ground cover is denseR; Not reusableP: Effectiveness reduced when rainyRT:Not effective where terrain is ruggedSS: Not for use within environmentally sensitive sitesW: Effectiveness reduced when windyReference: Sorbents for Liquid Hazardous Substance Cleanup and Control;	cross-linked polymer	- pillow		1		throw	pitchfork	R, DGC, RT
treated wood fiber - pillow3throwpifoamed glass - pillow4throwpiLAND SPILL - MEDIUM1blowerskiplocross-linked polymer - particulate1blowerskiplopolypropylene - particulate2blowerskiplosorbent clay - particulate2blowerskiplopolypropylene - mat3throwskiplopolypropylene - mat3blowerskiplopolyurethane - mat4throwskiplopolycropylene - mat4throwskiplopolycropylene - mat3blowerskiplopolycropylene - mat4throwskiplopolycropylene - mat4throwskiplopolycropylene - mat4throwskiplopolycropylene - mat3blowerskiplopolycropylene - mat4throwskiplopolycropylene - mat4throwskiplopolycropylene - mat4throwskiplopolycropylene - mat4throwskiploLegendDGC: Not effective where ground cover is denseskiploP: Effectiveness reduced when rainyRT:Not effective where terrain is ruggedS: Not for use within environmentally sensitive sitesskiploW: Effectiveness reduced when windyReference: Sorbents for Liquid Hazardous Substance Cleanup and Control;	sorbent clay - particu	late		2		shovel	shovel	R,I, P
foamed glass - pillow4throwpiLAND SPILL - MEDIUMcross-linked polymer - particulate1blowerskiplepolypropylene - particulate2blowerskiplesorbent clay - particulate2blowerskiplepolypropylene - mat3throwskipleexpanded mineral - particulate3blowerskiplepolyurethane - mat4throwskipleLegendDGC: Not effective where ground cover is denseR; Not reusableI: Not incinerableP: Effectiveness reduced when rainyRT:Not effective where terrain is ruggedSS: Not for use within environmentally sensitive sitesW: Effectiveness reduced when windyReference: Sorbents for Liquid Hazardous Substance Cleanup and Control;	wood fiber - pillow			3		throw	pitchfork	R, P, DGC, R
LAND SPILL - MEDIUM cross-linked polymer - particulate 1 blower skiple polypropylene - particulate 2 blower skiple sorbent clay - particulate 2 blower skiple polypropylene - mat 3 throw skiple expanded mineral - particulate 3 blower skiple polyurethane - mat 4 throw skiple Legend DGC: Not effective where ground cover is dense R; Not reusable is Not incinerable P: Effectiveness reduced when rainy RT:Not effective where terrain is rugged SS: Not for use within environmentally sensitive sites W: Effectiveness reduced when windy Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;	treated wood fiber - pi	illow		3		throw	pitchfork	DGC, RT
cross-linked polymer - particulate1blowerskiplepolypropylene - particulate2blowerskiplesorbent clay - particulate2blowerskiplepolypropylene - mat3throwskipleexpanded mineral - particulate3blowerskiplepolyurethane - mat4throwskipleDGC: Not effective where ground cover is denseR; Not reusableskipleI: Not incinerableP: Effectiveness reduced when rainyRT:Not effective where terrain is ruggedSS: Not for use within environmentally sensitive sitesW: Effectiveness reduced when windyReference: Sorbents for Liquid Hazardous Substance Cleanup and Control;	foamed glass - pillow			4		throw	pichfork	R, P, DGC, R
polypropylene - particulate 2 blower skiple sorbent clay - particulate 2 blower skiple polypropylene - mat 3 throw skiple expanded mineral - particulate 3 blower skiple polyurethane - mat 4 throw skiple Legend DGC: Not effective where ground cover is dense skiple P: Effectiveness reduced when rainy reusable skiple P: Effectiveness reduced when rainy skiple skiple SS: Not for use within environmentally sensitive sites W: Effectiveness reduced when windy Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;	LAND SPILL - MEDIU	M						
sorbent clay - particulate 2 blower skiple polypropylene - mat 3 throw skiple expanded mineral - particulate 3 blower skiple polyurethane - mat 4 throw skiple Legend DGC: Not effective where ground cover is dense 4 throw skiple DGC: Not effective where ground cover is dense 8 8 8 1 P: Effectiveness reduced when rainy 8 8 8 1 P: Effectiveness reduced when rainy 8 8 1 1 1 S: Not for use within environmentally sensitive sites 8 1 <td< td=""><td>cross-linked polymer</td><td>- particulate</td><td></td><td>1</td><td>blo</td><td>ower</td><td>skiploader</td><td>R,W, SS</td></td<>	cross-linked polymer	- particulate		1	blo	ower	skiploader	R,W, SS
polypropylene - mat 3 throw skiple expanded mineral - particulate 3 blower skiple polyurethane - mat 4 throw skiple Legend DGC: Not effective where ground cover is dense 4 throw skiple DGC: Not effective where ground cover is dense 8 8 8 1 P: Effectiveness reduced when rainy 8 8 8 1 1 P: Effective mess reduced when rainy 8 8 8 1 <td>polypropylene - parti</td> <td>culate</td> <td></td> <td>2</td> <td>blo</td> <td>ower</td> <td>kiploader</td> <td>W, SS, DGC</td>	polypropylene - parti	culate		2	blo	ower	kiploader	W, SS, DGC
expanded mineral - particulate 3 blower skiple polyurethane - mat 4 throw skiple Legend DGC: Not effective where ground cover is dense skiple P: Not reusable I: Not incinerable I: Not incinerable P: Effectiveness reduced when rainy RT:Not effective where terrain is rugged SS: Not for use within environmentally sensitive sites W: Effectiveness reduced when windy Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;	sorbent clay - particu	late		2	blo	ower	kiploader	R, I, W, P, DG0
polyurethane - mat 4 throw skiple Legend DGC: Not effective where ground cover is dense R; Not reusable R; Not reusable I: Not incinerable P: Effectiveness reduced when rainy R: Not for use within environmentally sensitive sites S: Not for use within environmentally sensitive sites W: Effectiveness reduced when windy Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;	polypropylene - mat			3	th	row s	kiploader	DGC, RT
Legend DGC: Not effective where ground cover is dense R; Not reusable I: Not incinerable P: Effectiveness reduced when rainy RT:Not effective where terrain is rugged SS: Not for use within environmentally sensitive sites W: Effectiveness reduced when windy Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;	expanded mineral - pa	articulate		3	blo	ower	kiploader	R, I, W, P, DG0
DGC: Not effective where ground cover is dense R; Not reusable I: Not incinerable P: Effectiveness reduced when rainy RT:Not effective where terrain is rugged SS: Not for use within environmentally sensitive sites W: Effectiveness reduced when windy Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;	polyurethane - mat			4	th	row s	skiploader	DGC, RT
 R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation Inderate hazard. Clear area of personnel and move upwind. 	CGC: Not effective wh R; Not reusable Not incinerable Effectiveness reduc R:Not effective where S: Not for use within V: Effectiveness redu Reference: Sorbents f R.W Melvold et al: Pol Moderate hazard.	ced when rain e terrain is ru environment ced when win for Liquid Haz lution Techno	ny gged ally sensitive sites ndy cardous Substance C logy Review No. 150				tion 1988	

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

 DO NOT allow clothing wet with material to stay in contact with skin Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. 	
Other information	 Material is hygroscopic, i.e. absorbs moisture from the air. Keep containers well sealed in storage. Store in original containers. Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

Suitable container	 Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	 Glycols and their ethers undergo violent decomposition in contact with 70% perchloric acid. This seems likely to involve formation of the glycol perchlorate esters (after scission of ethers) which are explosive, those of ethylene glycol and 3-chloro-1,2-propanediol being more powerful than glyceryl nitrate, and the former so sensitive that it explodes on addition of water. Alcohols are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents. reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil,
	triethylaluminium, triisobutylaluminium ▶ should not be heated above 49 deg.

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1		TEEL-2	TEEL-3	
propylene glycol	Propylene glycol; (1,2-Propanediol)	30 mg/m3		1300 mg/m3	7900 mg/m3	
Ingredient	Original IDLH		Revised IDLH			
propylene glycol	Not Available	Not Available				

MATERIAL DATA

for propylene glycol:

Saturated vapour concentration @ 20 deg C.= 65.8 ppm, 204.6 mg/m3; i.e higher concentrations can only occur as aerosols or at higher temperatures. Odour Threshold: Practically odourless.

A small number of individuals show skin irritation or sensitisation from repeated or prolonged exposure to propylene glycol. A workplace environmental exposure limit (WEEL) has been established by AIHA and is thought to be protective against systemic effects.

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.
Body protection	See Other protection below
Other protection	 Overalls. P.V.C. apron. Barrier cream.
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the: **"Forsberg Clothing Performance Index".** The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection: FW-WCH N&A Wild Cherry Flavor

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Material	CPI
PE/EVAL/PE	А

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion **NOTE**: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following

long-term or frequent use. A qualified practitioner should be consulted.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator	
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2	
up to 50 x ES	-	A-AUS / Class 1 P2	-	
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^	

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Clear colorless		
Physical state	Liquid	Relative density (Water = 1)	1.08
Odour	Characteristic	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	75.78	Taste	Wild Cherry
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Combustible.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

Continued...

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

	logical effects		
Inhaled	 The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of vapours, fumes or aerosols, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo. 		
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual. Ingestion of propylene glycol produced reversible central nervous system depression in humans following ingestion of 60 ml. Symptoms included increased heart-rate (tachycardia), excessive sweating (diaphoresis) and grand mal seizures in a 15 month child who ingested large doses (7.5 ml/day for 8 days) as an ingredient of vitamin preparation. Excessive repeated ingestions may cause hypoglycaemia (low levels of glucose in the blood stream) among susceptible individuals; this may result in muscular weakness, incoordination and mental confusion.		
Skin Contact	 Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. The material may produce moderate skin irritation; limited evidence or practical experience suggests, that the material either: produces moderate inflammation of the skin in a substantial number of individuals following direct contact and/or produces significant, but moderate, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. 		
Eye	Limited evidence exists, or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals and/or is expected to produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur. Irritation of the eyes may produce a heavy secretion of tears (lachrymation).		
Chronic	There exists limited evidence that shows that ski reaction in a significant number of individuals, ar		
FW-WCH N&A Wild Cherry Flavor	TOXICITY Not Available	IRRITATION Not Available	}
propylene glycol	TOXICITY Dermal (rabbit) LD50: >2000 mg/kg ^[1] Oral (rat) LD50: 20000 mg/kgd ^[2]	Eye (rabbit): Skin(human)	100 mg - mild 500 mg/24h - mild :104 mg/3d Intermit Mod :500 mg/7days mild
Legend:	1. Value obtained from Europe ECHA Registered Unless otherwise specified data extracted from F	-	
FW-WCH N&A Wild Cherry Flavor	The acute oral toxicity of propylene glycol is ve damage in humans. Serious toxicity generally of high intake over a relatively short period of tim or supplements, which contain at most 1 g/kg of inappropriate intravenous administration or acco oral toxicity is also low.	occurs only at plasma conce ne. It would be nearly impose of PG. Cases of propylene g	ntrations over 1 g/L, which requires extremely sible to reach toxic levels by consuming foods lycol poisoning are usually related to either
PROPYLENE GLYCOL	The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis. The acute oral toxicity of propylene glycol is very low, and large quantities are required to cause perceptible health damage in humans.		
	1 -		
Acute Toxicity	0	Carcinogenicity	0

Serious Eye Damage/Irritation	~	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0
		🗙 – Data avai	ired to make classification available lable but does not fill the criteria for classification Available to make classification

CMR STATUS

Not Applicable

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

NOT AVAILABLE

Ingredient	Endpoint	Test Duration	Effect	Value	Species	BCF
propylene glycol	Not Available					

Propylene glycol is known to exert high levels of biochemical oxygen demand (BOD) during degradation in surface waters. This process can adversely affect aquatic life by consuming oxygen needed by aquatic organisms for survival. Large quantities of dissolved oxygen (DO) in the water column are consumed when microbial populations decompose propylene glycol.

Sufficient dissolved oxygen levels in surface waters are critical for the survival of fish, macro-invertebrates, and other aquatic organisms.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
propylene glycol	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
propylene glycol	LOW (BCF = 1)

Mobility in soil

Ingredient	Mobility
propylene glycol	HIGH (KOC = 1)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate:
Product / Packaging	▶ Reduction
disposal	▶ Reuse
	▶ Recycling
	 Disposal (if all else fails)
	This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

propylene	"US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)", "US - Washington Toxic air pollutants and their ASIL,
glycol(57-55-6) is	SQER and de minimis emission values", "US AIHA Workplace Environmental Exposure Levels (WEELs)", "US Spacecraft
found on the	Maximum Allowable Concentrations (SMACs) for Airborne Contaminants", "US Toxic Substances Control Act (TSCA) -
following regulatory	Chemical Substance Inventory"
lists	

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Υ
Japan - ENCS	Y
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory $N = Not$ determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

